

# BPR303

## MIFARE READER WITH VOICE MESSAGE



- \* **3-5cm reading distance**
- \* **ISO14443 compliant**
- \* **Ability to select messages via RS232/RS485**
- \* **Remote access and management via GSM**
- \* **Driver (user) ID**
- \* **Can be linked to the role (Immobilizer)**
- \* **Suitable for access control applications**
- \* **ABS enclosure**
- \* **Competable with our vehicle trackers**
- \* **Pre-recorded audio messages**
- \* **Customized messages can be ordered**
- \* **Total capacity of 32 messages up to 64sec**



### **SPECIFICATIONS:**

- **ISO/IEC 14443 A/MIFARE**
- **13.56MHz**
- **3 –5 cm reading distance**
- **Open collector output**
- **Interface: RS232/RS485**
- **Operating voltage: 9-36 VDC**
- **Current: Max 300mA @ 12VDC**
- **Dimensions: 120x80x22,5 mm**
- **Weight: 75gr**
- **Rh: 80%**
- **Operating temp: -5°C ile +55°C**
- **Online operation**
- **Offline operation(Optional)**
- **120 users capacity**
- **0,5W audio output**
- **Total capacity of 32 messages up to 64sec**
- **Pre-recorded messages**
- **Configurable via GSM**
- **Buzzer**
- **IP54**

